



V-PREM-S

Ageing 1 temperature
wine cabinet
Premium Pack



Sliding shelf
ACMS

GENERAL FEATURES

| | Solid door | Glass door |
|---------------------------------------|--------------------|--------------------|
| Gross weight packaged (kg)* | 62 | 69 |
| Empty wine cabinet net weight (kg) | 49 | 56 |
| Equipped wine cabinet net weight (kg) | 63 | 70 |
| Dimensions H x W x D (mm) | 960 x 680 x 715 | 960 x 680 x 715 |
| Dimensions in pack H x W x D (mm) | 1090 x 720 x 760 | 1090 x 720 x 760 |
| Colors | Nero - RAL 9005 | Nero - RAL 9005 |
| Door profile colors | Black, Silver, Red | Black, Silver, Red |

TECHNICAL FEATURES

REGULATION

- On/ Off button
- Digital electronic controls
- Inner display and setting
- Temperature setting range from 9 to 15°C (default temperature setting : 12°C)
- LCD screen with touch buttons
- Visual and audible alarm in case of temperature disfunctioning (+ or - 6°C default temperature setting)

HOT – COLD – INSULATION TECHNOLOGIES

- | | |
|-----------------------------|--|
| Cold production: | <ul style="list-style-type: none"> • Static cooling • Compressor R600a/R134a |
| Cords: | <ul style="list-style-type: none"> • CE/UK/AU/CH/US |
| Hot production: | <ul style="list-style-type: none"> • Heating element |
| Hot release : | <ul style="list-style-type: none"> • Automatic • Threshold : adjustable |
| Inner material : | <ul style="list-style-type: none"> • Aluminium |
| Exterior coating material : | <ul style="list-style-type: none"> • HDF (High Density Fiber) |
| Insulation type: | <ul style="list-style-type: none"> • PU foam |

EQUIPMENTS & ACCESSORIES

EQUIPMENT

- Reversible solid or glass door
- Removable LED lighting system, fixed on an adhesive base (4 LED, battery operation: ref. AAA LR03)
- Charcoal filter
- Front adjustable feet
- Handle included in door frame
- Locking system
- 1 EuroCave key ring

ACCESSORIES

- 5 sliding shelves
- Overall capacity: 74 bottles**
- Sliding shelf capacity: 12 bottles

ENERGY EFFICIENCY AND CONSUMPTION

| Cords | 230V-50Hz (R600a) | | 115V-60Hz (R134a) | |
|---|-------------------|-------|-------------------|-------|
| | Glass | Solid | Glass | Solid |
| Doors type | Glass | Solid | Glass | Solid |
| Energy efficiency rating | A | A+ | / | / |
| Annual energy consumption AEc (kWh/year)*** | 146 | 114 | 183 | 146 |
| Useful volume (L) | 225 | 225 | 225 | 225 |
| Acoustic emissions (dB(A)) | 37 | 37 | 38 | 38 |
| Recommended T° range (°C) | 0-30 | 0-35 | 0-30 | 0-35 |

* Empty wine cabinet weight
 ** Traditional Bordeaux bottles
 *** Calculation based on the result obtained over 24 hrs in standard conditions (25°C / 77°F)